Vickers Laboratories Ltd - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.2

Revision date: Date printed: 16 April 2021 03 February 2023

005

Section 1. Identification

1	Product Identifier	0057
	Product Name	AMMONIUM DICHROMATE pure
	CAS Number REACH Registration No	7789-09-5 A registration number is not available as the substance or its uses are exempt, the annual tonnage does not require a registration or the registration is envisaged for a later date.
	Molecular Formula	$(NH_{4})_{2}Cr_{2}O_{7} = 252.06$

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier

1.4

1.1

Vickers Laboratories Ltd



Grangefield Industrial Estate Richardshaw Road Pudsey West Yorkshire LS28 6QW UNITED KINGDOM

Phone Fax Email Website	44 0113 2362811 +44(0)113 2362703 safety@viclabs.co.uk www.viclabs.co.uk
Emergency Telephone	(08:00-16:30) +44(0) 113 2362811
	(24hr) 112 (Have this document to hand)
	(nave uns document to nand)

Section 2. Hazards Identification


2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Oxidising solid, category 2	H272: May intensify fire; oxidizer.
Acute toxicity, category 2 (inhalation)	H330: Fatal if inhaled.
Acute toxicity, category 3 (oral)	H301: Toxic if swallowed.
Skin corrosion/irritation, category 1B	H314: Causes severe skin burns and eye damage.
Acute toxicity, category 4 (dermal)	H312: Harmful in contact with skin.
Respiratory sensitization, category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization, category 1	H317: May cause an allergic skin reaction.
Germ cell mutagenicity, category 1B	H340: May cause genetic defects.
Carcinogenicity, category 1B	H350: May cause cancer.
Reproductive toxicity, category 1B	H360: May damage fertility or the unborn child.
Spec target organ tox - repeat, category 1	H372: Causes damage to organs through prolonged or repeated exposure.
Hazard to aquatic environment, category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to regulation 1272/2008/EC



Section 3. Composition

3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Ammonium Dichromate	7789-09-5	232-143-1		>99%	Ox. Sol. 2,Acute Tox. 2 (I),Acute Tox. 3 (O),Skin Corr. 1B,Acute Tox. 4 (D),Resp. Sens. 1,Skin Sens. 1,Muta. 1B,Carc. 1B,Repr. 1B,STOT RE 1,Aquatic Chronic 1

Section 4. First Aid

4.1 Description of first aid measures

Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. Unless contact has been slight OBTAIN MEDICAL ATTENTION
Skin	Thoroughly wash off skin with soap and water. Remove contaminated clothing immediately and wash before re- use. Unless contact has been slight OBTAIN MEDICAL ATTENTION
Inhalation	Remove from exposure. Irrigate mouth and nasal passage with water. OBTAIN MEDICAL ATTENTION.
Ingestion	If conscious give several glasses of water to drink and 5-10g of ascorbic acid dissolved in water. Do not induce vomiting. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Personal protection for first aiders	Wear protective gloves / eye protection.

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media Extinguishing Media	Consider what other flammable materials are present and act accordingly.
Unsuitable Media	Nothing specified.
5.2 Special hazards arising fro	
Hazards	Can decompose explosively above 225C. Contact with combustible material may cause a fire.
5.3 Advice for firefighters	
Advice for firefighters	Fire-fighters should wear protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Avoid breathing dust-wear respiratory protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so.

6.2 Environmental precautions

Enviromental

Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs. Keep combustible material away from spillage.

6.3 Methods and material for containment and cleaning up

Major Spillage	Shovel/sweep up into container for removal Small areas of contamination should be treated with ferrous sulphate solution to reduce the chromium to the safer (trivalent) form and the pH adjusted to 8.5 prior to disposal. Wash area down with copious amounts of water.
Minor Spillage	Vacuum up into container for removal. Carefully remove material from vacuum cleaner and transfer to sealable container for disposal. Carry out this operation under fume extraction. Small areas of contamination should be treated with ferrous sulphate solution to reduce the chromium to the safer (trivalent) form and the pH adjusted to 8.5 prior to disposal. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not breath dust. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains dust concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Store in a suitable area for oxidising agents. Do not store on wooden surfaces. Keep well separated from combustible materials.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits	
			Long Term (8hr TW)	YA) Short Term 15min period)
Ammonium Dichromate	7789-09-5	>99%	-	- 0.05 ppm -

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

Respiratory Protection	Use L.E.V. or natural ventilation to maintain dust concentrations below exposure limits. If not, use a well maintained chemical cartridge respirator, or use self contained breathing apparatus.
Hand Protection	Use nitrile gloves or PVC gauntlets.
Eye Protection	Use tightly fitting chemical splash proof glasses or goggles.
Skin Protection	Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.
Special Hazards	No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance	Orange red crystals.
Odour	Odourless.
pН	4 @ 20°C solution.

Boiling Point	Not available
Melting Point	180°C
Flash Point	Not applicable
Upper Flammable Limit	Not applicable
Lower Flammable Limit	Not applicable
Auto Ignition	Not applicable
Explosive Properties	Exhibits explosive properties but fails to meet the acceptance criteria for a Class 1 explosive.
Oxidising Properties	Mildly oxidising in solution, strongly oxidising in strong acid solution.
Vapour Pressure	Not applicable
Relative Density	2.1500
Water Solubility	27%

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1	Reactivity	No data available.
10.2	Chemical Stability	Stable under normal conditions starts to decompose at 180C, becomes self sustaining at 225C.
10.3	Possibility of hazardous reactions	No data available.
10.4	Conditions to Avoid	Avoid exposure to heat.
10.5	Incompatable Materials	Many organic compounds. Combustible materials. Acids. Alkalis.
10.6	Hazardous Decomposition Products	None unusual. Decomposition begins at 180 C, with spontaneous ignition. Material swells greatly with evolution of heat and nitrogen

Section 11. Toxicological Information

11.1 Information on toxicological effects

.1 Intormation on toxicolo	gical circus
Eyes	The solid and solutions will cause severe irritation and corneal damage.
Skin	The solid and solutions will highly irritating and corrosive to the skin, local inflammation can occur from 5% solutions. Contact with broken skin may lead to ulcers especially on the hands and forearms. Can be absorbed through the skin and cause systemic poisoning and subsequent kidney damage. May cause sensitisation by skin contact.
LD50 Skin	1170mg/kg Rabbit
Ingestion	Ingestion will cause cause dental discolouration, nausea, vomiting, diarrhoea, and cardiovascular shock due to blood loss into the gastrointestinal tract. Necrosis of the liver and kidneys may also occur.
LD50 Oral	54mg/kg Rat
Inhalation	Inhalation of dust will produce severe irritation of the eyes, nose, throat and respiratory tract. Causes inflammation of the larynx, bronchitis, and ulceration of the nasal septum.
LD50 Inhalation	Not available
TCLo	Not available
Carcinogenicity	No information is available.
Mutagenicity	No information is available.
Reproductive Effects	No information is available.

Section 12. Ecological

12.1	Toxicity	Chromium (VI) will eventually be reduced to Chromium (III) by organic matter in water. Unlikely to bio- accumulate. Toxicity to fish-LC50 (Mosquito fish) 96hr - 136 mg/l. Very Toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment.		
	LC50 Algal	Not available		
	LC50 Crustacea	Not available		
	LC50 Fish	Not available		
12.2	Persistence and degradability	No data available.		

12.3	Bioaccumulative potential	No data available.
12.4	Mobility in soil	No data available.
12.5	Results of PBT & vPvB assessment	Assessment not required.
12.6	Other adverse effects	None known at present.

Section 13. Disposal Considerations

13.1 Waste treatment methods Disposal Methods

Never dispose of into water courses or sewerage systems. Treat with ferrous sulphate solution to reduce the chromium to the safer (trivalent) form. The pH should be adjusted to 8.5, with sodium hydroxide or sodium carbonate, prior to disposal.

Contaminated Packaging Use a licensed waste disposer.

Section 14. Transport Information

14.1	UN Number	1439	
14.2	Proper Shipping Name	Ammonium dichromate	
14.3	Transport classes UN classification Subsidiary hazard(s) Transport category ADR Hazard ID Tunnel Restriction Code	5.1 None 2 50 E	OXIDIZING AGENT 5.1
4.4	Packing Group	II	
14.5	Environment hazards	See section 12.	
14.6	Special precautions for user	No special precautions required.	
14.7	Transport in bulk	Not transported in bulk.	

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification	Oxidising solid, category 2; Acute toxicity, category 2 (inhalation); Acute toxicity, category 3 (oral); Skin corrosion/irritation, category 1B; Acute toxicity, category 4 (dermal); Respiratory sensitization, category 1; Skin sensitization, category 1; Germ cell mutagenicity, category 1B; Carcinogenicity, category 1B; Reproductive toxicity, category 1B; Spec target organ tox - repeat, category 1; Hazard to aquatic environment, category 1	
Signal word	Danger	
Hazard Pictograms		
Hazard Statements	H272, H350, H340, H360, H330, H301, H372, H312, H314, H334, H317, H410 May intensify fire; oxidizer. May cause cancer. May cause genetic defects. May damage fertility or the unborn child. Fatal if inhaled. Toxic if swallowed. Causes damage to organs through prolonged or repeated exposure. Harmful in contact with skin. Causes severe skin burns and eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects.	
Hazard Statements (Packs of 500ml/g or less)	H272, H350, H340, H360, H330, H301, H372, H312, H314 May intensify fire; oxidizer. May cause cancer. May cause genetic defects. May damage fertility or the unborn child. Fatal if inhaled. Toxic if swallowed. Causes damage to organs through prolonged or repeated exposure. Harmful in contact with skin. Causes severe skin burns and eye damage.	

Keep away from heat / sparks/open flames/hot surfaces - No smoking. Keep / Store away from clothing / combustible materials. Take any precaution to avoid mixing with combustibles... Wear protective gloves / protective clothing / eye protection.

Precautionary Statements (Packs of 500ml/g or less) P210, P220, P280

 $Keep\ away\ from\ heat\ /\ sparks/open\ flames/hot\ surfaces\ -\ No\ smoking.\ Keep\ /\ Store\ away\ from\ clothing\ /\ combustible\ materials.\ Wear\ protective\ gloves\ /\ protective\ clothing\ /\ eye\ protection.$

15.2 Chemical safety assessment

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.2 (Supercedes revision 1.1)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 03 February 2023

Copyright: 2023 Vickers Laboratories Ltd