Vickers Laboratories Ltd - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 2.0 (Replaces revision 1.1 of 16 April 2021) Revision date: Date printed: 18 June 2021 03 February 2023

107

Section 1. Identification

1.1	Product Identifier	1070
	Product Name	NITAL ETCH SOLUTION 5% v/v
	CAS Number REACH Registration No	Mixture A registration number is not available as the substance or its uses are exempt, the annual tonnage does not require a registration or the registration is envisaged for a later date.

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier

1.4

VICKERS

Vickers Laboratories Ltd Grangefield Industrial Estate Richardshaw Road Pudsey West Yorkshire LS28 6QW UNITED KINGDOM

	Phone Fax Email Website	44 0113 2362811 +44(0)113 2362703 safety@viclabs.co.uk www.viclabs.co.uk	
Ļ	Emergency Telephone	(08:00-16:30) +44(0) 113 2362811	
		(24hr) 112	2
		(Have this document to hand)	

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Flammable liquid, category 2 Acute toxicity, category 3 (oral) Acute toxicity, category 3 (dermal) Skin corrosion/irritation, category 1B Acute toxicity, category 3 (inhalation) Spec target organ tox - single, category 1 H225: Highly flammable liquid and vapour.
H301: Toxic if swallowed.
H311: Toxic in contact with skin.
H314: Causes severe skin burns and eye damage.
H331: Toxic if inhaled.
H370: Causes damage to organs.


2.2 Label elements

Labelling according to regulation 1272/2008/EC

Signal word

Danger

Hazard Pictograms



Section 3. Composition

3.2 Mixtures

Component C	JAS NO.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Methanol	67-56-1	200-659-6	01-2119433307-44-XXXX	~95%	Flam. Liq. 2, Acute Tox. 3 (O), Acute Tox. 3 (D), Acute Tox. 3 (I), STOT SE 1
Nitric acid 7	697-37-2	231-714-2	01-2119487297-23-XXXX	~5%	Ox. Liq. 3, Skin Corr. 1A, Acute Tox. 3 (I)

Section 4. First Aid

4.1 Description of first aid measures

1	
Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION.
Skin	Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. OBTAIN MEDICAL ATTENTION URGENTLY.
Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Ingestion	If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Personal protection for first aiders	Wear protective gloves / eye protection.

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media	Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.
Unsuitable Media	Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards

Vapour-air mixtures are explosive.

5.3 Advice for firefighters

Advice for firefighters

Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so.

6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage	Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.
Minor Spillage	Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits			
			Long Term (8hr	TWA)	Short Term 15mi	n period)
Methanol	67-56-1	~95%	200.0 ppm	266.0 mg/m-3	250.0 ppm	333.0 mg/m-3
Nitric acid	7697-37-2	~5%	-	-	1.0 ppm	2.8 mg/m-3

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

Respiratory Protection	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.
Hand Protection	Use solvent resistant gloves.
Eye Protection	Use tightly fitting chemical splash proof glasses or goggles.
Skin Protection	Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.
Special Hazards	No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance	Clear colourless liquid.
Odour	Fresh and characteristic.
pH	Not applicable

Boiling Point	Not available
Melting Point	Not applicable
Flash Point	Not applicable
Upper Flammable Limit	Not applicable
Lower Flammable Limit	Not applicable
Auto Ignition	Not applicable
Explosive Properties	Moderate/severe in confined spaces.
Oxidising Properties	No.
Vapour Pressure	Not applicable
Relative Density	Not available
Water Solubility	Completely miscible in water.

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1	Reactivity	No data available.
10.2	Chemical Stability	Stable under normal conditions
10.3	Possibility of hazardous reactions	No data available.
10.4	Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
10.5	Incompatable Materials	Bromine. Sodium hypochlorite, diethyl zinc, dialkylaluminium solutions, and phosphorous trioxide. Nitric acid, hydrogen peroxide, sodium and chloroform and potassium tertiary butoxide. Lead perchlorate.
10.6	Hazardous Decomposition Products	None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Section 11. Toxicological Information

11.1 Information on toxicological effects

I mormation on toxicologica	
Eyes	Both the vapour and liquid are, very dangerous to the eyes since methanol has a specific effect on the optic nerve and retina.
Skin	Repeated exposure may cause dermatitis. Many of the effects typical of the vapour can result from absorbtion through the skin.
LD50 Skin	Not available
Ingestion	Ingestion will cause symptoms resembling those of alcoholic intoxication is excitation and irritability. After a latent period of 10-15 hours more serious damage to the central nervous system especially to the optic nerve occurs. Even if death does not occur permanent blindness may occur.
LD50 Oral	Not available
Inhalation	Exposure to vapour concentrations above the occupational exposure limits may cause headache, nausea, vomiting and irritation of the mucous membranes. High concentrations of vapour may damage the central nervous system and cause blindness. Due to the slow metabolism of the toxic metabolites formic acid and formaldehyde the effects can be cumulative and continued exposure to low levels may cause the above effects.
LD50 Inhalation	Not available
TCLo	Not available
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	High vapour concentrations (10000 ppm) caused increased congenital malformations.

Section 12. Ecological

12.1 Toxicity Substantially biodegradable in water, biological oxygen demand (E to the aerobic treatment process at 39500mg/l but evidence of inhib 79000mg/l.		Substantially biodegradable in water, biological oxygen demand (B.O.D.) 5 day 70%. No evidence of inhibition to the aerobic treatment process at 39500mg/l but evidence of inhibition occurs at concentrations greater than 79000mg/l.
	LC50 Algal	Not available
	LC50 Crustacea	Not available
	LC50 Fish	Not available

12.2	Persistence and degradability	No data available.
12.3	Bioaccumulative potential	No data available.
12.4	Mobility in soil	No data available.
12.5	Results of PBT & vPvB assessment	Assessment not required.
12.6	Other adverse effects	None known at present.

Section 13. Disposal Considerations

13.1 Waste treatment methods Disposal Methods

Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging

Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

4.1 UN Number	1230	
4.2 Proper Shipping Name	Methanol	
4.3 Transport classes UN classification Subsidiary hazard(s) Transport category	3 6.1 2	FLAMMABLE LIQUID 3 6.1
ADR Hazard ID Tunnel Restriction Code	336 D/E	▼
4.4 Packing Group	II	
4.5 Environment hazards	See section 12.	
4.6 Special precautions for user	No special precautions required.	
4.7 Transport in bulk	Not transported in bulk.	

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification	Flammable liquid, category 2; Acute toxicity, category 3 (oral); Acute toxicity, category 3 (dermal); Skin corrosion/irritation, category 1B; Acute toxicity, category 3 (inhalation); Spec target organ tox - single, category 1
Signal word	Danger
Hazard Pictograms	
Hazard Statements	H225, H314, H301+H311+H331, H370 Highly flammable liquid and vapour. Causes severe skin burns and eye damage. Toxic if swallowed, inhaled and in contact with skin. Causes damage to eyes & central nervous system.
Precautionary Statements	P210, P280, P260, P270, P403+P235, P233 Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection. Do not breathe fume/vapours. Do not eat, drink or smoke when using this product. Store in a well ventilated place. Keep cool. Keep container tightly closed.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 2.0 (Supercedes revision 1.1)

Revision date: 18 June 2021

Reviewed by chemist: 18 June 2021

Printed date: 03 February 2023

Copyright: 2023 Vickers Laboratories Ltd