Vickers Laboratories Ltd - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.0

Revision date: Date printed: 29 September 2021 03 February 2023

1 4

Section 1. Identification

1.1	Product Identifier	1159
	Product Name	TAPPI KIT 9 OIL MIXTURE
	CAS Number REACH Registration No	Mixture A registration number is not available as the substance or its uses are exempt, the annual tonnage does not require a registration or the registration is envisaged for a later date.
1.2 F		ne substance or mixure & uses advised against
	Uses of Material	Chemical for industrial and laboratory use. Not suitable for domestic use.
1.3	Supplier	Vickers Laboratories Ltd
	VICKERS LABORATORIES	Grangefield Industrial Estate Richardshaw Road Pudsey West Yorkshire LS28 6QW UNITED KINGDOM
	Phone Fax Email Website	44 0113 2362811 +44(0)113 2362703 safety@viclabs.co.uk www.viclabs.co.uk
1.4	Emergency Telephone	(08:00-16:30) +44(0) 113 2362811 (24hr) 112 (Have this document to hand)

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Flammable liquid, category 2 Skin corrosion/irritation, category 2 Reproductive toxicity, category 2 Spec target organ tox - single, category 3 Spec target organ tox - repeat, category 2 Aspiration hazard, category 1 Hazard to aquatic environment, category 1 Hazard to aquatic environment, category 1

- H225: Highly flammable liquid and vapour.
- H315: Causes skin irritation.
- H361: Suspected of damaging fertility or the unborn child.
- H336: May cause drowsiness or dizziness.
- H373: May cause damage to organs through prolonged or repeated exposure.
- H304: May be fatal if swallowed and enters airways.
- H400: Very toxic to aquatic life.
- H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to regulation 1272/2008/EC

Danger

Signal word

Hazard Pictograms



Section 3. Composition

3.2 Mixtures

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Toluene	108-88-3	203-625-9	01-2119471310-51-XXXX	40%	Flam. Liq. 2,Skin Irrit. 2,Repr. 2,STOT SE 3 (D),STOT RE 2,Asp. Tox. 1
n-Heptane	142-82-5	205-563-8	01-2119457603-38-XXXX	40%	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3 (D), Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1

Section 4. First Aid

4.1 Description of first aid measures

·····	
Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION.
Skin	Thoroughly wash off skin with soap and water. Remove contaminated clothing immediately and wash before re- use. In severe cases or if exposure has been great, OBTAIN MEDICAL ATTENTION.
Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Ingestion	If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Personal protection for first aiders	Wear protective gloves / eye protection.

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media Alcohol resistant foam, dry powder, carbon dioxide or vaporising liquid. Use water spray to keep fire exposed containers cool.

Unsuitable Media Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Vapour-air mixtures are explosive.

5.3 Advice for firefighters

Hazards

Advice for firefighters

Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus.

6.1 Personal precautions, protective equipment and emergency procedures

······································	
Personal Protection	Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware : vapour is heavier than air and will tend to accumulate at low spots.
6.2 Environmental precautions	
Enviromental	Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage	Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.
Minor Spillage	Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage. Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits			
			Long Term (8hr	TWA)	Short Term 15mi	n period)
Toluene	108-88-3	40%	50.0 ppm	191.0 mg/m-3	100.0 ppm	384.0 mg/m-3
n-Heptane	142-82-5	40%	500.0 ppm	-	1500.0 ppm	-

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

Respiratory Protection	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.
Hand Protection	Use solvent resistant gloves.
Eye Protection	Use tightly fitting chemical splash proof glasses or goggles.
Skin Protection	Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.
Special Hazards	No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Odour	Characteristic aromatic odour.
pH	Not applicable
Boiling Point	Not available
Melting Point	Not applicable
Flash Point	Not applicable
Upper Flammable Limit	Not applicable
Lower Flammable Limit	Not applicable
Auto Ignition	Not applicable
Explosive Properties	Severe in confined spaces.
Oxidising Properties	No.
Vapour Pressure	Not applicable
Relative Density	0.8104
Water Solubility	Insoluble in water.

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1	Reactivity	No data available.
10.2	Chemical Stability	Stable under normal conditions
10.3	Possibility of hazardous reactions	No data available.
10.4	Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
10.5	Incompatable Materials	Strong oxidising agents.
10.6	Hazardous Decomposition Products	None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Section 11. Toxicological Information

11.1 Information on toxicological effects

8	
Eyes	Both the vapour and liquid will, act as an eye irritant. Repeated exposure to the vapours can lead to reversible corneal changes and conjunctivitis
Skin	Repeated or prolonged contact may defat the skin producing irritation and dermatitis. Skin penetration is possible. May cause skin sensitisation.
LD50 Skin	Not available
Ingestion	The liquid causes damage to stomach and intestinal linings.
LD50 Oral	Not available
Inhalation	Exposure to vapour concentrations above the occupational exposure limits will cause narcosis. Prolonged exposure to vapour concentrations above the occupational exposure limits will cause headache, nausea, vomiting and irritation of the mucous membranes. High concentrations of vapour may produce central nervous system depression and unconsciousness.
LD50 Inhalation	Not available
TCLo	Not available
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	May be a mutagen.
Reproductive Effects	It is considerably embryotoxic, but only weakly teratogenic with a low incidence of malformations.

Section 12. Ecological

12.1	Toxicity	Moderately toxic to mammals, fish and bacteria.
	LC50 Algal	Not available
	LC50 Crustacea	Not available
	LC50 Fish	Not available
12.2	Persistence and degradability	No data available.

Vickers Laboratories Ltd - Safety Data Sheet

12.3	Bioaccumulative potential	No data available.
12.4	Mobility in soil	No data available.
12.5	Results of PBT & vPvB assessment	Assessment not required.
12.6	Other adverse effects	None known at present.

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1	UN Number	1993	
14.2	Proper Shipping Name	Flammable liquid, N.O.S. (Toluene, Heptane)	,h,
14.3	Transport classes UN classification Subsidiary hazard(s) Transport category	3 None 2	FLAMMABLE
	ADR Hazard ID Tunnel Restriction Code	33 D/E	3
14.4	Packing Group	П	
14.5	Environment hazards	See section 12.	
14.6	Special precautions for user	No special precautions required.	
14.7	Transport in bulk	Not transported in bulk.	

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification	Flammable liquid, category 2; Skin corrosion/irritation, category 2; Reproductive toxicity, category 2; Spec target organ tox - single, category 3; Spec target organ tox - repeat, category 2; Aspiration hazard, category 1; Hazard to aquatic environment, category 1; Hazard to aquatic environment, category 1
Signal word	Danger
Hazard Pictograms	
Hazard Statements	H225, H315, H373, H304, H336, H361 Highly flammable liquid and vapour. Causes skin irritation. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child.
Precautionary Statements	P233, P280, P261, P301+P310, P331 Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection. Avoid breathing dust / fume / gas / mist / vapours / spray. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.0

Revision date: 29 September 2021

Reviewed by chemist: 29 September 2021

Printed date: 03 February 2023

Copyright: 2023 Vickers Laboratories Ltd