Vickers Laboratories Ltd - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.2 Revision date: 28 April 2021 Date printed: 03 February 2023

Section 1. Identification

1.1 Product Identifier 2857

Product Name BORON TRIFLUORIDE-METHANOL COMPLEX

CAS Number Mixture

REACH Registration No A registration number is not available as the substance or its uses are exempt, the

annual tonnage does not require a registration or the registration is envisaged for a

later date.

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier Vickers Laboratories Ltd

VICKERS

Grangefield Industrial Estate

Richardshaw Road

Pudsey West Yorkshire

LS28 6QW

UNITED KINGDOM

 Phone
 44 0113 2362811

 Fax
 +44(0)113 2362703

 Email
 safety@viclabs.co.uk

 Website
 www.viclabs.co.uk

1.4 Emergency Telephone (08:00-16:30) +44(0) 113 2362811

(24hr) 112

(Have this document to hand)

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Flammable liquid, category 2 H225: Highly flammable liquid and vapour.

Acute toxicity, category 3 (oral)

Acute toxicity, category 3 (dermal)

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

Skin corrosion/irritation, category 1B H314: Causes severe skin burns and eye damage.

Acute toxicity, category 3 (inhalation) H331: Toxic if inhaled.

Spec target organ tox - single, category 1 H370: Causes damage to organs.

2.2 Label elements

Labelling according to regulation 1272/2008/EC

Signal word Danger

Hazard Pictograms









Hazard Statements Highly flammable liquid and vapour. Toxic if swallowed, inhaled and in contact with skin. Causes severe skin

burns and eye damage. Causes damage to organs.

Precautionary Statements Keep away from heat / sparks/open flames/hot surfaces - No smoking. Keep container tightly closed.

Ground/bond container and receiving equipment. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue

rinsing

Section 3. Composition

3.2 Mixtures

| Component | CAS No. | EEC No. | REACH No. | Conc w/w | CLP Classification (1272/2008/CE) |
|---|---------|-----------|-----------------------|----------|---|
| Methanol | 67-56-1 | 200-659-6 | 01-2119433307-44-XXXX | >50% | Flam. Liq. 2,Acute Tox. 3 (O),Acute Tox. 3 (D),Acute Tox. 3 (I),STOT SE 1 |
| Boron trifluoride - methanol complex | Mixture | | | ~20% | Flam. Liq. 2,Acute Tox. 3 (O),Acute Tox. 3 (D),Skin Corr. 1B,Acute Tox. 3 (I),STOT SE 1 |

Section 4. First Aid

4.1 Description of first aid measures

Eyes Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL

ATTENTION.

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If

breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery

position. OBTAIN MEDICAL ATTENTION URGENTLY.

Ingestion If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen

if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the

recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Personal protection for first Wear protective gloves / eye protection.

aiders

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed

containers cool.

Unsuitable Media Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards Vapour-air mixtures are explosive.

5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate

area immediately. Do not allow general use of area until it is safe to do so.

6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local

Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with

copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in

remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage. Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

| Component | CAS No | Concentration | Workplace Exposure Limits | | | | |
|---|---------|---------------|---------------------------|--------------|--------------------------|--------------|--|
| | | | Long Term (8hr TWA) | | Short Term 15min period) | | |
| Methanol | 67-56-1 | >50% | 200.0 ppm | 266.0 mg/m-3 | 250.0 ppm | 333.0 mg/m-3 | |
| Boron trifluoride - methanol complex | Mixture | ~20% | - | - | - | - | |

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance Clear yellow solution.

Odour Characteristic. pН Not applicable **Boiling Point** Not available Melting Point Not applicable

16°C Flash Point

Upper Flammable Limit 36.5% (V) Methanol Lower Flammable Limit 5.5% (V) Methanol **Auto Ignition** Not applicable

Explosive Properties Moderate/severe in confined spaces.

Oxidising Properties

Vapour Pressure 4hPa @ 20°C Relative Density 0.89g/cm3 @ 20°C Water Solubility Not available

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1 Reactivity No data available.

10.2 Chemical Stability Stable under normal conditions

Reacts vigorously with strong oxidising agents (eg nitrates, chlorates, perchlorates and peroxides) Explosive; mass explosion hazard. Contamination by incompatible substances can initiate exothermic decomposition. 10.3 Possibility of hazardous

reactions

10.4 Conditions to Avoid Hot surfaces, naked flames or other sources of ignition.

10.5 Incompatable Materials Bromine. Sodium hypochlorite, diethyl zinc, dialkylaluminium solutions, and phosphorous trioxide. Nitric acid,

hydrogen peroxide, sodium and chloroform and potassium tertiary butoxide. Lead perchlorate.

10.6 Hazardous Decomposition None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Products

Section 11. Toxicological Information

11.1 Information on toxicological effects

Eyes Both the vapour and liquid are, very dangerous to the eyes since methanol has a specific effect on the optic nerve

and retina. May damage the central nervous system and cause blindness.

Causes burns. Repeated exposure may cause dermatitis. Many of the effects typical of the vapour can result from Skin

absorbtion through the skin.

LD50 Skin 300mg/kg Acute toxicity estimate

Ingestion Ingestion will cause symptoms resembling those of alcoholic intoxication ie excitation and irritability. After a

latent period of 10-15 hours more serious damage to the central nervous system especially to the optic nerve occurs. Even if death does not occur permanent blindness may occur. Causes severe burns. Symptoms may include salivation, thirst, difficulty in swallowing, pain, shock and vomiting. Liver and kidney damage may also

occur.

LD50 Oral 100mg/kg Acute toxicity estimate

Inhalation Exposure to vapour concentrations above the occupational exposure limits may cause headache, nausea, vomiting

and irritation of the mucous membranes. High concentrations of vapour may damage the central nervous system

and cause blindness.

LD50 Inhalation 3mg/l Acute toxicity estimate

TCLo Not available

Carcinogenicity Not considered to be a carcinogen. Mutagenicity Not considered to be a mutagen.

Reproductive Effects High vapour concentrations (10000 ppm) caused increased congenital malformations.

Section 12. Ecological

Substantially biodegradable in water, biological oxygen demand (B.O.D.) 5 day 70%. No evidence of inhibition 12.1 Toxicity

to the aerobic treatment process at 39500mg/l but evidence of inhibition occurs at concentrations greater than

79000mg/l.

LC50 Algal Not available LC50 Crustacea Not available

Vickers Laboratories Ltd - Safety Data Sheet Ref: 2857 LC50 Fish Not available

12.2 Persistence and degradability No data available.

12.3 Bioaccumulative potential No data available.

12.4 Mobility in soil No data available.

12.5 Results of PBT & vPvB Assessment not required.

assessment

12.6 Other adverse effects None known at present.

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of

into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1 UN Number 2924

14.2 Proper Shipping Name Flammable liquid, corrosive, N.O.S. (Cont.

Methanol, Boron trifluoride-methanol complex)

14.3 Transport classes

UN classification 3
Subsidiary hazard(s) 8
Transport category 2
ADR Hazard ID 38
Tunnel Restriction Code D/E
Packing Group III

14.4 Packing Group III

14.5 Environment hazards See section 12.

14.6 Special precautions for No special precautions required.

user

14.7 Transport in bulk Not transported in bulk.

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Flammable liquid, category 2; Acute toxicity, category 3 (oral); Acute toxicity, category 3 (dermal); Skin

corrosion/irritation, category 1B; Acute toxicity, category 3 (inhalation); Spec target organ tox - single, category 1

Signal word Danger

Hazard Pictograms









CORROSIVE

Hazard Statements H225, H301+H311+H331, H314, H370

Highly flammable liquid and vapour. Toxic if swallowed, inhaled and in contact with skin. Causes severe skin

burns and eye damage. Causes damage to organs.

Precautionary Statements P210, P233, P240, P301+P330+P331, P304+P340, P305+P351+P338

Keep away from heat / sparks/open flames/hot surfaces - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing.

15.2 Chemical safety assessment

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.2 (Supercedes revision 1.1)

Revision date: 28 April 2021

Reviewed by chemist: 28 April 2021

Printed date: 03 February 2023

Copyright: 2023 Vickers Laboratories Ltd