# Vickers Laboratories Ltd - Safety Data Sheet

3092

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.1 Revision date: 16 April 2021 Date printed: 03 February 2023

Section 1. Identification

1.1 Product Identifier 3092

Product Name CRUDE OIL (ARTIFICIAL)

CAS Number Mixture

REACH Registration No A registration number is not available as the substance or its uses are exempt, the

annual tonnage does not require a registration or the registration is envisaged for a

later date.

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier Vickers Laboratories Ltd

VICKERS

Grangefield Industrial Estate

Richardshaw Road

Pudsey West Yorkshire LS28 6QW

UNITED KINGDOM

 Phone
 44 0113 2362811

 Fax
 +44(0)113 2362703

 Email
 safety@viclabs.co.uk

 Website
 www.viclabs.co.uk

**1.4 Emergency Telephone** (08:00-16:30) +44(0) 113 2362811

(24hr) 112

(Have this document to hand)

### Section 2. Hazards Identification

#### 2.1 Classification of the substance or mixture

Carcinogenicity, category 1B

#### Classification according to regulation 1272/2008/EC

Flammable liquid, category 2 H225: Highly flammable liquid and vapour.

Skin corrosion/irritation, category 2

H315: Causes skin irritation.
Serious eye damage/irritation, category 2

H319: Causes serious eye irritation.

Respiratory sensitization, category 1 H334: May cause allergy or asthma symptoms or breathing difficulties if

H350: May cause cancer.

inhaled.

Aspiration hazard, category 1 H304: May be fatal if swallowed and enters airways. Hazard to aquatic environment, category 2 H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

#### Labelling according to regulation 1272/2008/EC

Signal word Danger

Hazard Pictograms







Hazard Statements Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause allergy or

asthma symptoms or breathing difficulties if inhaled. May cause cancer. May be fatal if swallowed and enters

airways. Toxic to aquatic life with long lasting effects.

Precautionary Statements Keep away from heat / sparks/open flames/hot surfaces - No smoking. Keep container tightly closed. Wear

protective gloves / protective clothing / eye protection. Store in a well ventilated place. Keep cool. Do not breathe

fume/vapours.

# Section 3. Composition

#### 3.2 Mixtures

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Mixed hydrocarbon solvent	64742-47- 8	265-149-8		~20%	Asp. Tox. 1
White spirit	8052-41-3	265-191-7		10.4%	Flam. Liq. 3,Skin Irrit. 2,STOT RE 1,Asp. Tox. 1,Aquatic Chronic 3
Mixed hydrocarbon solvent	8032-32-4	232-453-7		~3%	Flam. Liq. 1,Skin Irrit. 2,Repr. 2,STOT SE 3 (D),Asp. Tox. 1,Aquatic Chronic 2
Mixed hydrocarbon solvent	8032-32-4	232-453-7	01-2119473851-33-XXXX	~3%	Flam. Liq. 2,Skin Irrit. 2,Repr. 2,STOT SE 3 (D),Asp. Tox. 1,Aquatic Chronic 2

# Section 4. First Aid

#### 4.1 Description of first aid measures

Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. If discomfort persists OBTAIN MEDICAL ATTENTION. Eyes

Skin Thoroughly wash off skin with soap and water. Remove contaminated clothing immediately and wash before re-

Inhalation Remove from exposure.

Ingestion Wash out the patients mouth thoroughly with water. In severe cases or if exposure has been great, OBTAIN

MEDICAL ATTENTION.

Personal protection for first Wear protective gloves / eye protection.

aiders

### 4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

# **Section 5. Fire Fighting**

#### 5.1 Extinguishing media

Extinguishing Media Foam, dry powder, carbon dioxide or vaporising liquids.

Unsuitable Media Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards Presents no specific fire danger.

#### 5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus.

# Section 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection See section 8.2 for information on protective equipment and section 13 for information on disposal.

#### 6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local

Environmental Health Officer if major spillage occurs.

#### 6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Wash area down with detergent

and copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Wash area down with detergent

and copious amounts of water.

#### 6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

# Section 7. Storage & Handling

#### 7.1 Precautions for safe handling

No specific precautions.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well ventilated place. Keep container tightly closed.

#### 7.3 Specific end use(s)

See section 1.2.

# Section 8. Workplace Exposure & Personal Protection

#### 8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits					
			Long Term (8hr TWA)		Short Term 15min period)			
Refined mineral oil	8042-47-5	58.8%	-	-	5.0 ppm	10.0 mg/m-3		
Mixed hydrocarbon solvent	64742-47-8	~20%	-	-	-	-		
White spirit	8052-41-3	10.4%	100.0 ppm	125.0 mg/m-3	575.0 ppm	720.0 mg/m-3		
Petroleum spirit 60/80 a.r.		~4.5%	-	-	-	-		
Mixed hydrocarbon solvent	8032-32-4	~3%	250.0 ppm	-	-	-		
Mixed hydrocarbon solvent	8032-32-4	~3%	240.0 ppm	-	-	-		

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

### 8.2 Exposure controls

Respiratory Protection Store in a well ventilated place. Keep container tightly closed. Use in well ventilated area. In case of inadequate

ventilation wear respiratory protection.

Hand Protection Wear gloves

Eye Protection Use tightly fitting chemical splash proof glasses or goggles.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

# Section 9. Physical & Chemical Properties

#### 9.1 Information on basic physical and chemical properties

Appearance Black / brown oily liquid

Odour Characteristic. pН Not applicable 165°C **Boiling Point** Melting Point Not applicable Flash Point 60°C (Closed cup) Upper Flammable Limit Not applicable Lower Flammable Limit Not applicable Auto Ignition Not applicable

Explosive Properties No. Oxidising Properties No.

Vapour Pressure Not applicable Relative Density 0.8300

Water Solubility Insoluble in water.

#### 9.2 Other information

No data available.

# Section 10. Stability & Reactivity

**10.1** Reactivity No data available.

**10.2** Chemical Stability Stable under normal conditions

**10.3** Possibility of hazardous

reactions

No data available.

10.4 Conditions to Avoid No specific conditions.10.5 Incompatable Materials Strong oxidising agents.

10.6 Hazardous Decomposition None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

**Products** 

# Section 11. Toxicological Information

# 11.1 Information on toxicological effects

Eyes Causes serious eye irritation.

Skin Causes skin irritation.

LD50 Skin Not available

Ingestion Acts as a laxative if taken internally. May be fatal if swallowed and enters airways.

LD50 Oral Not available

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

LD50 Inhalation Not available
TCLo Not available
Carcinogenicity May cause cancer.

Mutagenicity Not considered to be a mutagen.

Reproductive Effects None identified.

Other Information Limit exposure.

# Section 12. Ecological

**12.1** Toxicity Limited biodegradability when tested by CEC-L-33-T-82 (50%) but regarded as inherently biodegradable.

Leeching and penetration through surface soils is generally regarded as resulting in long term persistence. Fresh

or used product may be harmful to aquatic life.

LC50 Algal Not available
LC50 Crustacea Not available
LC50 Fish Not available

**12.2** Persistence and degradability

No data available.

**12.3** Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

Results of PBT & vPvB

assessment

Assessment not required.

**12.6** Other adverse effects

None known at present.

# **Section 13. Disposal Considerations**

#### 13.1 Waste treatment methods

Disposal Methods Dispose of in a licensed incinerator. Contaminated Packaging Use a licensed waste disposer.

# **Section 14. Transport Information**

14.1 UN Number 1267

14.2 Proper Shipping Name Petroleum crude oil

14.3 Transport classes

UN classification 3 Subsidiary hazard(s) None Transport category 3 ADR Hazard ID 30 **Tunnel Restriction Code** D/E

14.4 Packing Group

14.5 Environment hazards See section 12.

14.6 Special precautions for

No special precautions required.

14.7 Transport in bulk

Not transported in bulk.

# Section 15. Regulatory Information

### 15.1 Safety, health and environment regulations specific for subtance/mixture.

# Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Flammable liquid, category 2; Skin corrosion/irritation, category 2; Serious eye damage/irritation, category 2;

Respiratory sensitization, category 1; Carcinogenicity, category 1B; Aspiration hazard, category 1; Hazard to aquatic

environment, category 2

Signal word Danger

Hazard Pictograms







Hazard Statements H225, H315, H319, H334, H350, H304, H411

> Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause cancer. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Precautionary Statements P210, P233, P280, P403+P235, P260

> Keep away from heat / sparks/open flames/hot surfaces - No smoking. Keep container tightly closed. Wear protective gloves / protective clothing / eye protection. Store in a well ventilated place. Keep cool. Do not breathe

fume/vapours.

# 15.2 Chemical safety assessment

Assessment not required.

# Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supercedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 03 February 2023

Copyright: 2023 Vickers Laboratories Ltd